

# T5 High Output

## F39T5/841/HO/ALTO 40PK

Philips T5 HO lamps are environmentally-responsible, ultra-slim and have extraordinary light output and longer life.

### Product data

General Information	
Cap-Base	G5 [ G5]
Life to 50% Failures Preheat (Nom)	30000 h
Features	HO Alto® [ High Output Alto]
System Description	HO [ High Output (HO)]
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
LSF Preheat 16000 h Rated	97 %
LSF Preheat 20000 h Rated	84 %
Light Technical	
Color Code	841 [ CCT of 4100K]
Luminous Flux (Nom)	3500 lm
Luminous Flux (Rated) (Nom)	3100 lm
Color Designation	Cool White (CW)
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	92 lm/W
Correlated Color Temperature (Nom)	4100 K
Luminous Efficacy (rated) (Nom)	82 lm/W
Color Rendering Index (Max)	85
Color Rendering Index (Min)	80
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %


LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %
Operating and Electrical	
Power (Rated) (Nom)	38.0 W
Lamp Current (Nom)	0.325 A
Temperature	
Design Temperature (Nom)	35 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	Green [ Green Base]
Bulb Shape	T5 [ 16 mm (T5)]
Approval and Application	
Mercury (Hg) Content (Nom)	1.4 mg
Product Data	
Order product name	39W/841 Min Bipin T5 HO ALTO UNP

# T5 High Output

EAN/UPC - Product	046677290252
Order code	290254
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	927992684022

Net Weight (Piece)	78.000 g
ILCOS Code	FDH-39/40/1B-L/P-G5-16/1150



## Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
39W/841 Min Bipin T5 HO	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm
ALTO UNP					

TL5 HO F39T5/841 HO Alto



## Photometric data



Lightcolor /840

Lightcolor /840

## Lifetime




MASTER TL5 HO/ActiViva Life Expectancy 3 h cycle

MASTER TL5 HO/ActiViva Life Expectancy 12 h cycle

## T5 High Output

### Lifetime



MASTER TL5 HO/ActiViva Lumen Maintenance 3 h + 12 h cycle

