



Pulse Start Metal Halide Standard

MS400/BU/ED28/PS 12PK

Philips Pulse Start Metal Halide Lamps offer an optimized metal halide system for greater efficiency and lumen maintenance.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Product data

General information	
Cap-Base	E39 [Single Contact Mogul Screw]
Operating Position	Base Up +/- 15 D [Base Up +/- 15 D]
Main Application	General Lighting (G)
Life to 50% Failures (Nom)	20000 h
ANSI Code HID	M155/M135/E
System Description	Pulse Start
Light technical	
Color Code	640 [CCT of 4000K]
Luminous Flux (Rated) (Min)	42000 lm
Luminous Flux (Rated) (Nom)	44000 lm
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	385
Chromaticity Coordinate Y (Nom)	390
Correlated Color Temperature (Nom)	4000 K


Luminous Efficacy (Rated) (Min)	105 lm/W
Luminous Efficacy (rated) (Nom)	110 lm/W
Color Rendering Index (Nom)	68
Operating and electrical	
Lamp Current (Nom)	3.2 A
Ignition Supply Voltage (Min)	254 V
Re-Ignition Time (Min) (Max)	6 min
Voltage (Max)	150 V
Voltage (Min)	120 V
Voltage (Nom)	135 V
Mechanical and housing	
Bulb Finish	Clear
Cap-Base Information	Nic/Brass [Nickel/Brass Base]
Bulb Material	Hard Glass

Pulse Start Metal Halide Standard

Bulb Shape	ED28 [ED28]
Approval and application	
Mercury (Hg) Content (Nom)	50 mg
Luminaire design requirements	
Bulb Temperature (Max)	450 °C
Cap-Base Temperature (Max)	230 °C
Product data	
Order product name	Pulse Start MH Std 400W/640 CW Mog ED28 1SL

EAN/UPC - Product	046677232528
Order code	232520
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601165501
Net Weight (Piece)	0.001 kg

Dimensional drawing



Product	D	C (max)
Pulse Start MH Std 400W/640 CW Mog ED28 1SL	3.5 in	8.3 in

Pulse Start MH Std 400W/640 CW Mog ED28 1SL

