



T8

9.9T8/COR/48-850/MF16/G 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000X
Technical Type	9.9-32W
Light Technical	
Color Code	850 [CCT of 5000K]
Beam Angle (Nom)	240 °
Luminous Flux (Nom)	1650 lm
Luminous Flux (Rated) (Nom)	1650 lm
Color Designation	Daylight [Daylight]
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	166.00 lm/W
Color Consistency	<5
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	9.9 W
Lamp Current (Max)	100 mA
Lamp Current (Min)	43 mA
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
UL Type	Type B - bypass the ballast
Power Factor (Nom)	0.9
Voltage (Nom)	120-277 V
Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	70 °C

T8

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Material	Glass
Product Length	1200 mm
Bulb Shape	Tube, double-ended


Approval and Application

Energy Saving Product	Yes
Approval Marks	RoHS compliance UL certificate
Energy Consumption kWh/1000 h	- kWh

Product Data

Order product name	9.9T8/COR/48-850/MF16/G 10/1
EAN/UPC - Product	046677557447
Order code	557447
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002326104
Net Weight (Piece)	0.240 kg


Dimensional drawing




TLED T8 120-277V 9.9-32W 1650lm 5000K

Product	D1	D2	A1	A2	A3
9.9T8/COR/48-850/MF16/G 10/1	25.7 mm	28 mm	1198 mm	1205 mm	1212 mm

Photometric data




LEDtube 9,9W G13 850



LEDtube 9,9W G13


Photometric data



Technical Parameters 43 Page 17


LEDtube 9,9W G13 850

Lifetime



LEDtube 50K-LED

LEDtube 50K FailureRate-LED



LEDtube 9,9W G13 LumenVsTc

LEDtube 50K-LMP

Lifetime



LEDtube 50K LifetimeVsTc-LED

